
FnIO G – Series :

GT-3958

GT-3958 (8 Channels 18pt RTB, Differential Current Input)

0~30mA / -30~30mA, 12bit

Table of Contents

[Table of Contents.....2](#)

[History.....3](#)

[1.Environment Specification.....4](#)

[2.GT-3958 \(8 Channels, Differential Current Input, 0~30mA / -30~30mA, 12bit\).....5](#)

[2.1.GT-3958 Specification.....5](#)

[2.2.GT-3958 Wiring Diagram.....6](#)

[2.3.GT-3958 LED Indicator.....7](#)

[2.3.1.LED Indicator.....7](#)

[2.3.2.Channel Status LED.....7](#)

[2.4.Data Value / Current.....8](#)

[2.4.1.Operating Range.....8](#)

[2.4.2.Underrun / Overrun Range.....9](#)

[2.5.Mapping Data into the Image Table.....9](#)

[2.6.Parameter Data.....10](#)

History

Rev	Pages	Remarks	Date	Editor
1.00			2025/04/17	Soyeong, Park

Specification

1. Environment Specification

Environmental Specification	
Operation Temperature	-40°C ~60°C
UL Temperature	-20°C ~60°C
Non-Operating Temperature	-40°C ~85°C
Relative Humidity	5% ~ 90% Non-condensing
Mounting	DIN rail
General Specification	
Shock Operating	IEC 60068-2-27
Vibration Resistance	Based on IEC 60068-2-6, 4g
Industrial Emissions	EN61000-6-4/All : 2011
Industrial Immunity	EN 61000-6-2 : 2019
Installation Position	Vertical and horizontal installation is available
Product Certifications	CE, UKCA, UL


Specification

2. GT-3958 (8 Channels, Differential Current Input, 0~30mA / -30~30mA, 12bit)

2.1. GT-3958 Specification

Items	Specification
Input Specification	
Inputs Per Module	8 Channels Differential, non-isolated between channel
Indicators	1 Green G-Bus status
Resolution in Ranges	12 bits : 7.32uA/bit(0~30mA) 12 bits : 14.65uA/bit(-30~30mA)
Input Range	0~30mA, -30~30mA
Data Format	16bits Integer (2' compliment)
Module Error	±0.1% Full Scale @ 25°C ±0.3% Full Scale @ -40°C, 60°C
Input Impedance	80Ω
Conversion Time	2.2msec / All channel
Calibration	Not Required
General Specification	
Power Dissipation	Max. 250mA @ 5Vdc
Isolation	I/O to Logic : Photocoupler Isolation Field power : Not Connected
UL Field Power	Supply Voltage : 24Vdc nominal, Class 2
Field Power	Not used, Field power bypass to next expansion module
Single Wiring	I/O Cable Max. 0.823mm ² (AWG 18)
Weight	63g
Module Size	12mm x 109mm x 70mm
Environment Condition	Refer to 'Environment Specification'


2.2. GT-3958 Wiring Diagram



Pin No.	Signal Description
0	Input Channel 0(+)
1	Input Channel 0(-)
2	Input Channel 1(+)
3	Input Channel 1(-)
4	Input Channel 2(+)
5	Input Channel 2(-)
6	Input Channel 3(+)
7	Input Channel 3(-)
8	Input Channel 4(+)
9	Input Channel 4(-)
10	Input Channel 5(+)
11	Input Channel 5(-)
12	Input Channel 6(+)
13	Input Channel 6(-)
14	Input Channel 7(+)
15	Input Channel 7(-)
16	Input Channel Common(AGND)
17	Input Channel Common(AGND)

2.3. GT-3958 LED Indicator

2.3.1. LED Indicator



LED No.	LED Function / Description	LED Color
0	Status LED	Green

2.3.2. Channel Status LED

Status	LED	To indicate
G-Bus Status	Off Green	Disconnection Connection


Specification

2.4. Data Value / Current

2.4.1. Operating Range


Current Range : 0~30mA

Current	0.0mA	10.0mA	15.0mA	30.0mA
Data(Hex)	H0000	H0555	H07FF	H0FFF



Current Range : -30~30mA

Current	-30.0mA	-15.0mA	0mA	15.0mA	30.mA
Data(Hex)	HF800	HFC00	H0000	H03FF	H07FF



Specification


2.4.2. Underrun / Overrun Range

Current	Current Range : 0~30mA		Current Range : -30~30mA	
	<0.0mA	>31.0mA	<-31.0mA	>31.0mA
Data(Hex)	-	H7FFF	H8000	H7FFF

2.5. Mapping Data into the Image Table

● Input Module Data

Analog Input Ch0
Analog Input Ch1
Analog Input Ch2
Analog Input Ch3
Analog Input Ch4
Analog Input Ch5
Analog Input Ch6
Analog Input Ch7



● Input Image Value

Bit No	Bit7	Bit6	Bit5	Bit4	Bit3	Bit2	Bit1	Bit0
Byte0	Analog Input Ch0 Low byte							
Byte1	Analog Input Ch0 High byte							
Byte2	Analog Input Ch1 Low byte							
Byte3	Analog Input Ch1 High byte							
Byte4	Analog Input Ch2 Low byte							
Byte5	Analog Input Ch2 High byte							
Byte6	Analog Input Ch3 Low byte							
Byte7	Analog Input Ch3 High byte							
Byte8	Analog Input Ch4 Low byte							
Byte9	Analog Input Ch4 High byte							
Byte10	Analog Input Ch5 Low byte							
Byte11	Analog Input Ch5 High byte							
Byte12	Analog Input Ch6 Low byte							
Byte13	Analog Input Ch6 High byte							
Byte14	Analog Input Ch7 Low byte							
Byte15	Analog Input Ch7 High byte							

2.6. Parameter Data

- Valid Parameter length: 10 Bytes
- Parameter Data

Bit No	Bit 7	Bit 6	Bit 5	Bit 4	Bit 3	Bit 2	Bit 1	Bit 0
Byte0	Ch#0 Command(H00 : 0~30mA, H01 : -30~30mA)							
Byte1	Ch#1 Command(H00 : 0~30mA, H01 : -30~30mA)							
Byte2	Ch#2 Command(H00 : 0~30mA, H01 : -30~30mA)							
Byte3	Ch#3 Command(H00 : 0~30mA, H01 : -30~30mA)							
Byte4	Ch#4 Command(H00 : 0~30mA, H01 : -30~30mA)							
Byte5	Ch#5 Command(H00 : 0~30mA, H01 : -30~30mA)							
Byte6	Ch#6 Command(H00 : 0~30mA, H01 : -30~30mA)							
Byte7	Ch#7 Command(H00 : 0~30mA, H01 : -30~30mA)							
Byte8	Filter Time(H00 : Default Filter(20), H01 : Fastest ~ H3E : Slowest, HFF : Filter OFF)							
Byte9	Reserved							