
FnIO G – Series :

GT-2368

GT-2368 (8 Points, Source Output Terminal, 24Vdc, Multi-Com)

Specification

Table of Contents

Table of Contents.....2

History.....3

1.ENVIRONMENT SPECIFICATION.....4

2.GT-2368 (8 Points, Source Output Terminal).....5

 2.1.GT-2368 Specification.....5

 2.2.GT-2368 Wiring Diagram.....6

 2.3.GT-2368 LED Indicator.....7

 2.3.1.LED Indicator.....7

 2.3.2.Channel Status LED.....7

 2.4.Mapping data into the image table.....8

 2.5.Parameter Data.....9

Specification

History

Rev	Pages	Remarks	Date	Editor
1.00			2017/10/16	Hongseok, Kim
1.01	6	Change Diagram, Point	2023/04/03	Soyeong, Park
1.02	4,6,7,8,9	Edit Certification, Mapping data, Parameter data / Change Diagram, Status LED	2023/08/08	Suna, Hwang

Specification

1. ENVIRONMENT SPECIFICATION

Environmental specification	
Operation Temperature	-40°C ~60°C
UL Temperature	-20°C ~60°C
Storage Temperature	-40°C ~85°C
Relative Humidity	5%~90% Non-condensing
Mounting	DIN Rail
General specification	
Shock Operating	IEC 60068-2-27
Vibration Resistance	Based on IEC 60068-2-6, 4g
Industrial Emissions	EN61000-6-4/All : 2011
Industrial Immunity	EN 61000-6-2 : 2019
Installation Position	Vertical and horizontal installation is available
Product Certifications	CE, UL


Specification

2. GT-2368 (8 Points, Source Output Terminal)

2.1. GT-2368 Specification

Items	Specification
Input specification	
Output per module	8 points source type
Indicators	8 green output status
Output voltage range	24Vdc nominal 15Vdc ~ 28.8Vdc
On-state voltage drop	0.3Vdc @ 25°C 0.5Vdc @ 60°C
On-state min. current	Min. 1mA
Off-state leakage current	Max. 5uA
Output signal delay	OFF to ON : Max. 0.3ms ON to OFF : Max. 0.5ms
Output current rating	Max. 0.5A per channel / Max. 4.0A per unit
Protection	Over current limit: Min. 3.5A @ 25°C per each channels Thermal shutdown : Min 3A @ 25°C per each channels Short circuit protection
Common type	8 points / 10 COM
General specification	
Power dissipation	Max. 50mA @ 5Vdc
Isolation	I/O to Logic : photocoupler isolation Field power : non-isolation
UL field power	Supply voltage : 24Vdc nominal, Class 2
Field power	Supply voltage : 24Vdc nominal Voltage range : 15~28.8Vdc Power dissipation: 35mA @ 24Vdc
Single Wiring	I/O Cable Max. 0.823mm ² (AWG 18)
Weight	65g
Module size	12mm x 109mm x 70mm
Environment condition	Refer to '1. Environment Specification'


2.2. GT-2368 Wiring Diagram



Pin No.	Signal Description
0	Output Channel 0
1	Common (Field Power 0V)
2	Output Channel 1
3	Common (Field Power 0V)
4	Output Channel 2
5	Common (Field Power 0V)
6	Output Channel 3
7	Common (Field Power 0V)
8	Output Channel 4
9	Common (Field Power 0V)
10	Output Channel 5
11	Common (Field Power 0V)
12	Output Channel 6
13	Common (Field Power 0V)
14	Output Channel 7
15	Common (Field Power 0V)
16	Common (Field Power 0V)
17	Field Power 24V

2.3. GT-2368 LED Indicator

2.3.1. LED Indicator



LED No.	LED Function / Description	LED Color
0	OUTPUT Channel 0	Green
1	OUTPUT Channel 1	Green
2	OUTPUT Channel 2	Green
3	OUTPUT Channel 3	Green
4	OUTPUT Channel 4	Green
5	OUTPUT Channel 5	Green
6	OUTPUT Channel 6	Green
7	OUTPUT Channel 7	Green


2.3.2. Channel Status LED

Status	LED	To indicate
No Signal	Off	No Output Signal
On Signal	Green	Output Signal detected

2.4. Mapping data into the image table

● Output Image Value

Bit No	Bit7	Bit6	Bit5	Bit4	Bit3	Bit2	Bit1	Bit0
Byte0	D7	D6	D5	D4	D3	D2	D1	D0



● Output Module Data

D7	D6	D5	D4	D3	D2	D1	D0
----	----	----	----	----	----	----	----

2.5. Parameter Data

- Valid Parameter length: 2 Bytes
- Parameter Data

Bit No	Bit7	Bit6	Bit5	Bit4	Bit3	Bit2	Bit1	Bit0
Byte0	Fault Action (ch0~ch7) 0: Fault value, 1:Hold last state							
Byte1	Fault value (ch0~ch7) 0:Off, 1:On							